



SUGGESTED USES:

- Bolts
- Screws
- Fittings

TECHNICAL SHEET

No. 646

FASLUB® SCREW LOOSE PENETRATING LUBRICANT

Screw loose penetrates rust corrosion, grease and dirt to loosen frozen parts. It leaves a graphite film to lubricate and protect metal surfaces.

CHARACTERISTICS:

Safe on paint and plastics. Contains no silicone. 360° valve sprays in any position

PACKAGING :

UPC Code	777954125348
Cans per case	12
Shipping weight per case	- Lbs.
Product weight	340 g.

DIRECTIONS :

Shake can well. Spray in the area to be treated and saturate. Use extension tubes for hard to reach areas.

PROPERTIES :

Physical State	Aerosol
Odour	Hydrocarbon Odor
Colour	Green
Vapour Density (Air=1)	> 1
Vapour Pressure (Psig)	50-60 Psig
Evaporation Rate	Slower Than N-Butyl Acetate
Boiling Point (Deg C)	176 C
Solubility in Water (% W/W)	Negligible
Specific Gravity	Liquid: 0.75-0.80 Aerosol: 0.65-0.70



6500, rue Zéphirin-Paquet,
Parc industriel Armand Viau
Québec (Québec) Canada G2C 0M3

1 800 463-5259
www.prdistribution.ca