

CARBON STEEL T-BOLT CLAMPS



Product Information

Heavy Duty T-Bolt with a stainless steel band and carbon steel bolt and housing have a wide variety of uses such as hydraulic suction and discharge and suction hose assemblies. These clamps are used where gear clamps do not provide adequate strength. They have a large size range and are tightened with a standard socket wrench. The band has a beveled edge which helps to prevent damage to the hose cover when tightened.

Notes

Please Note: Check the hose O.D. before ordering

Parts No.	Size Range Inches Min.	Size Range Inches Max.	Approx Weight	Torque Ft Lbs	Band Width
TBOLTC-17-19	22/32	24/32	0.090	4	3/4
TBOLTC-20-22	25/32	28/32	0.094	4	3/4
TBOLTC-23-25	29/32	1	0.095	4	3/4
TBOLTC-26-28	1-1/32	1-3/32	0.099	4	3/4
TBOLTC-29-31	1-5/32	1-7/32	0.121	7	3/4
TBOLTC-32-35	1-9/32	1-12/32	0.143	7	3/4
TBOLTC-36-39	1-13/32	1-17/32	0.154	7	3/4
TBOLTC-40-43	1-18/32	1-22/32	0.163	7	3/4
TBOLTC-44-47	1-23/32	1-27/32	0.183	7	3/4
TBOLTC-48-51	1-28/32	2	0.205	7	3/4
TBOLTC-52-55	2-2/32	2-5/32	0.209	7	3/4
TBOLTC-56-59	2-7/32	2-10/32	0.220	7	3/4
TBOLTC-60-63	2-11/32	2-15/32	0.227	7	3/4
TBOLTC-64-67	2-17/32	2-20/32	0.282	15	3/4
TBOLTC-68-73	2-22/32	2-28/32	0.352	15	1
TBOLTC-74-79	2-29/32	3-3/32	0.361	15	1
TBOLTC-80-85	3-5/32	3-10/32	0.383	15	1
TBOLTC-86-91	3-12/32	3-18/32	0.385	15	1
TBOLTC-92-97	3-20/32	3-26/32	0.403	15	1
TBOLTC-98-103	3-27/32	4-2/32	0.418	15	1
TBOLTC-104-112	4-3/32	4-12/32	0.440	26	1
TBOLTC-113-121	4-14/32	4-24/32	0.453	26	1
TBOLTC-122-130	4-25/32	5-4/32	0.460	26	1
TBOLTC-131-139	5-4/32	5-16/32	0.506	26	1
TBOLTC-140-148	5-16/32	5-28/32	0.682	26	1
TBOLTC-149-161	5-28/32	6-12/32	0.711	26	1
TBOLTC-162-174	6-12/32	6-28/32	0.726	26	1
TBOLTC-175-187	6-28/32	7-12/32	0.774	26	1
TBOLTC-188-200	7-12/32	7-28/32	0.825	26	1